

电磁屏蔽可旋转接头 EMC Straight fitting with swivel



材质：尼龙 66，黄铜镀镍螺纹

Material: Polyamide 66, Nickel plated brass thread

颜色：黑色 / 灰色

Colour: Black(BL) / Grey(GR)

温度：-45°C~+120°C，短时间 150°C

Temperature range: -45°C ~ +120°C, short-term to 150°C

防护等级：IP66, IP68(与软管及 RLS 密封垫配合使用)

Protection Degree: IP66, IP68(For use with conduits & RLS seal)

特性：高屏蔽和低耦合阻力，能屏蔽电信号和磁场等干扰信号，便于快速安装，并能紧固所穿电缆。适用于偶然的旋转。

Properties: High shielding alternation and low coupling resistance. Disturbance signals such as electrical signals and magnetic fields will be discharged to the housing/casing. Easy and quick installation. Fasten the cable. Suitable for occasional rotation.



CE UL测试 EN45545

M 螺纹

适配软管尺寸 Fits to Conduit size	型号 Part no.	螺纹 A Thread	B	C	D	E	F	G	包装(个) Packing
28	RL28-M25-CS90-X/EMV-11	M25X1.5	12.0	71.5	36.5	14.8	36.0	80.5	50
28	RL28-M25-CS90-X/EMV-7	M25X1.5	7.0	66.5	36.5	14.8	36.0	80.5	50
34	RL34-M32-CS90-X/EMV-12	M32X1.5	13.0	89.0	43.0	21.8	42.0	100.5	20
34	RL34-M32-CS90-X/EMV-8	M32X1.5	8.0	84.0	43.0	21.8	42.0	100.5	20
42	RL42-M40-CS90-X/EMV-13	M40X1.5	13.0	100.5	53.0	29.8	50.0	119.5	20
42	RL42-M40-CS90-X/EMV-8	M40X1.5	8.0	95.5	53.0	29.8	50.0	119.5	20
54	RL54-M50-CS90-X/EMV-14	M50X1.5	14.0	114.5	66.0	39.8	60.0	133.5	10
54	RL54-M50-CS90-X/EMV-9	M50X1.5	9.0	109.5	66.0	39.8	60.0	133.5	10